Information for users EN

EN 420:2003+A1:2009 EN 388:2016 PPE CATEGORY II

Read the instructions carefully.

In accordance with the requirements of the Regulation (EU) 2016/425.

Product:	t: Five-fingered gloves,		s, knitted fabric, poly	urethane (PU)	thane (PU) coating.	
Design:	"CITA"	Code:	3630 001 700 00 X	X Size:	6, 7, 8, 9, 10, 1	

Design:	"CITA"	Code:	3630 001 700 00 XX	Size:	6, 7, 8, 9, 10, 11	Production design:	C1001
Material:	terial: Palm: PU - Polyurethane coating, Liner (Palm, back and cuff): 64% 400D UHMWPE= Ultra-High Molecular Weight Polyethylene;						
21% 140D Nylon; 15% Elastane (100D SPANDEX), Binding: polyester.							

Purpose: These gloves are suitable for work with sharp object, glass etc. Do not use these gloves where protection is required in cuffs. We recommend that you keep this information for future reference. Put the gloves on dry, clean hands.

recommend that you keep this information for rature reference. I at the gloves on ary, clean hands.							
The gloves were tested in accordance with EN 388 - mechanical hazards (The higher the number, the higher the protection factor)							
A (0-4)	Abrasion resistance:	Performance level 4		The protection works only against the specified			
B (0-5)	Blade cut resistance	Performance level 3	Ĭ (ぱ <u>╒</u>)	hazards. Do not use the gloves as a protection against different hazards and classes. The results apply only for the model classes, not for the protection levels (classes). The protection levels (classes) are determined based on the tests carried out in accordance with the conditions determined in the valid standards specified here.			
C (0-4)	Tear resistance	Performance level 4					
D (0-4)	Puncture resistance	Performance level 3					
E (A-F)	Cut Resistance (TDM)	Performance level C	A.B.C.D.E.F.				
F(P/X) or nothing	Impact protection	Performance level X]				
EN 420 - protectiv	re gloves (general requirements)	As for the gloves with two or more layers it does					
(1-5) De	5) Dexterity			not necessarily reflect the properties of the outer			
,,X" = test not per	formed or not applicable	layer.					

Please note: The user must check the gloves before and after use to verify that they are in the required condition. Do not use as a protection against different hazards and classes. Do not use for manipulating hot or heated objects, toxic chemicals or greasy objects. Gloves material may be damaged by oil, mineral oil, greasy and solvent organic. Not resistant to soaking. It is not allowed to wear these gloves in cases with risk of entanglement with moving parts of machines. Due to the dulling of the blade during the cut resistance test (B) the results of the cut tests are only indicative, while the TDM (E) cut resistance test is the result of the reference design. The gloves comply with the requirements for puncture resistance. However, they are not meant for protection against thin, sharp objects, such as injection needles.

The mentioned facts may help the user for rational use of this type of protective gloves. It is the responsibility of every user to judge, whether the gloves are used in suitable conditions.

Maintenance, lifetime: After use, make sure the gloves are removed from all pollutants. Thus, you will extend their lifespan. The gloves are designed for single or short-term use only. Dry a damp muff further away from sources of heat at the room temperature. Washing or dry cleaning is not recommended. Any dirt should be brushed out using a soft brush. Do not clean chemically, bleach, dry in a tumble dryer, or iron. Worn through, burned through, strongly fouled or stiffened pairs have to be replaced with new ones. We are not responsible for any reduction of the protective function due to incorrect care. Under suitable storage conditions, shelf life is 2 years.

Storing and transport: Storing in a clean, dry and ventilated place at the room temperature, without any contamination by moisture, dirt, mould, or other agents reducing the level of protection. Do not expose it to solar radiation. The supplier doesn't provide warranty for such damage. Carry them preferably in original package.

Accessories: The product is supplied without accessories.

Dangerous admixtures: Materials which come into contact with the user's skin can cause an allergic reaction in sensitive individuals. Contains traces of DMF in compliance with occupational exposure limits.

If skin irritation or allergic reaction contact your doctor immediately.

Disposal: Dispose of used gloves with respect of the soiling level according to the applicable disposal regulations and the regulations of the local authority. Unused gloves can be disposed of with domestic waste.

The Notified Body that performs conformity assessment:

Notified Body No. 0075, CTC 4 rue Hermann Frenkel 69367 Lyon cedex 07 France.

The Declaration of Conformity can be found here: www.canis.cz; for individual products, in the bar "Documents to download".

Marking - example:			
"CITA"	Type of gloves		167
9	Size		64% 400D UHMWPE, 21% 140D nylon, 15% elastan(100D Spandex) / 64% 400D
EN388	Pictogram and number of the standard that the product complies with	CITA	ha diam a pistoch / Polydrethane on the pain
4343C	Results of the tests carried out		and fingers / poliuretan w dłońi i palcach
CE	Conformity mark		
cat II	Glove category	EN420 EN38	3
(i)	Symbol indicating the necessity to read the instructions	CE cat II 43430	
"SN"	Production identification	7	3630 001700 06 SN 74/2018/229
C1001	Production design	7	(ACMINISTRATION OF ACTION
ZA/2018/229	Lot		8 591940 060060
(Cos	Manufacturer identification		

