EN 420+A1:2009

EN 388:2016

PPE CATEGORY II

 $\square$ 

Read the instructions carefully.

In accordance with the requirements of the Regulation (EU) 2016/425.

**Product:** Textile gloves with print, palm and fingers nitrile coats.

Design:	"FIDO	Code:	3410 004 999 XX	Size:	7, 8, 9, 10, 11
Material:	100% Polyester, coating Nitrile.				

Purpose: They may serve as a protection of hands against dirt and protection in the working areas where workers have to face minor mechanical hazards (abrasions, soiling...), for example when electronics industry/ precision assembly, packing, inspection, cleanroom / automotive assembly, small parts handling. Put the gloves on dry, clean hands.

The gloves we	ere tes	ted in accordance with EN 388 - me	echanical hazards (The	e hi	igher the numb	er, the higher the protection factor)
A (0-4)		Abrasion resistance:	Performance level	3		The protection works only against
B (0-5)		Blade cut resistance (coupe test)	Performance level	1	( <u>ı=</u> )	hazards. Do not use the gloves as
C (0-4) D (0-4) E (A-F)		Tear resistance	Performance level Performance level Performance level	1	A.B.C.D.E.F	against different hazards and or results apply only for the model cla the protection levels (classes). The levels (classes) are determined by tests carried out in accordance conditions determined in the val
		Puncture resistance				
		Cut Resistance (TDM)				
F(P/X) or nothing		Impact protection	Performance level	X		
EN 420 - prote	ective	specified here. As for the gloves				
(1-5)	Dex	terity	Performance level 5	5		more layers it does not necessaril
,,X'' = test not performed or not applicable.						properties of the outer layer. T

The protection works only against the specified hazards. Do not use the gloves as a protection against different hazards and classes. The results apply only for the model classes, not for the protection levels (classes). The protection levels (classes) are determined based on the tests carried out in accordance with the conditions determined in the valid standards specified here. As for the gloves with two or more layers it does not necessarily reflect the properties of the outer layer. The protection levels (classes) apply only for new gloves not washed or cleaned.

Please note: The user must check the gloves before and after use to verify that they are in the required condition. Do not use as a protection against different hazards and classes. Do not use the gloves for handling with sharp objects, flames or hot or heated objects, toxic chemicals or greasy objects. Not resistant to soaking.

It is not allowed to wear these gloves in cases with risk of entanglement with moving parts of machines. Due to the dulling of the blade during the cut resistance test (B) the results of the cut tests are only indicative, while the TDM (E) cut resistance test is the result of the reference design. The gloves comply with the requirements for puncture resistance. However, they are not meant for protection against thin, sharp objects, such as injection needles. The mentioned facts may help the user for rational use of this type of protective gloves. It is the responsibility of every user to judge, whether the gloves are used in suitable conditions.

Maintenance, lifetime: After use, make sure the gloves are removed from all pollutants. Thus, you will extend their lifespan. The gloves are designed for single or short-term use only. Dry a damp muff further away from sources of heat at the room temperature. Maximal wash bath temperature 30 °C. Any dirt should be brushed out using a soft brush. Do not clean chemically, bleach, dry in a tumble dryer, or iron. Worn through, burned through, strongly fouled or stiffened pairs have to be replaced with new ones. We are not responsible for any reduction of the protective function due to incorrect care. Under suitable storage conditions, shelf life is 2 years.

Storing and transport: Storing in a clean, dry and ventilated place at the room temperature, without any contamination by moisture, dirt, mould, or other agents reducing the level of protection. Do not expose it to solar radiation. The supplier doesn't provide warranty for such damage. Carry them preferably in original package.

**Accessories:** The product is supplied without accessories.

Dangerous admixtures: The gloves may contain an allergen - Latex. They may cause an allergic reaction if used by sensitive people, including anaphylactic shock. If skin irritation or allergic reaction do not use gloves and contact your doctor immediately.

Disposal: Dispose of used gloves with respect of the soiling level according to the applicable disposal regulations and the regulations of the local authority. Unused gloves can be disposed of with domestic waste.

The Notified Body that performs conformity assessment:

Notified Body No. 0075, CTC 4 rue Hermann Frenkel 69367 Lyon cedex 07 France.

The Declaration of Conformity can be found here: www.canis.cz; for individual products, in the bar "Documents to download".

Marking - examp	le:	<i>,</i>	
"FIDO"	Type of gloves		
8	Size	FIDO	
EN 388	Pictogram and number of the standard that the product complies with	<b>FIDO</b> 3410 004 999 08	ZA/2019/225 A
3121X	Results of the tests carried out		
C€	Conformity mark	EN388	8   5 9 1 9 4 0   0 7 5 1 8 7   CANIS SAFETY a.s.
cat II	Glove category	(E 🕮 😉	Podebradská 260/59, Hloubětín, 198 00 PRAHA 9, Czech Republic
Ţį.	Notice on the necessity to read the instructions for use	cat II 3121X	
,,A"	Production identification		
ZA/2019/225	Lot		
(Cosi	Manufacturer identification		